

## 'Ariane' Haul-Off

### Main Characteristics

- **Haul-off length** : 300 mm to 2000 mm
- **Belt width** : 30 to 120 mm (standard)
- **Frame support** : spads and/or castors
- **Belt driven on multi 'V' grooves** rollers
- **Closing system** : mechanical or pneumatic

### Options

- **Various covering**
- **Specific guides** according to the product shape
- **Scowling Length Measure device**
- **Closing Travelling indicator or clamping pressure indicator.**
- **Deported Control of extrusion speed .**
- **Others** : according to customer's specifications.

- **200 mm to 400 mm Haul-off**
- **Belt width** : 20 to 45 mm
- **Mechanical or pneumatic closing device**

> Applications : **delicate products**  
(i.e : cathéters, small cables)

**Range** : AR02-30 / AR03-35 / AR04-50



Photo AR03-35

- **600 mm to 1000 mm Haul-off**
  - **Belt width** : 80 to 120 mm
  - **Mechanical or pneumatic closing device**
- > Applications : **flexible or rigid products**

**Range** : AR06-80 / AR06-100/AR06-120  
AR08-80/ AR08-100/ AR08-120  
AR100-100/AR100-120



Photo AR06-80

- **1200 mm to 2000 mm Haul-off**
- **Belt width** : 120 to 200 mm
- **Mechanical or hydraulic closing device**

> Applications : **strong sections Profiles or pipes**

**Range** : AR12-120 / AR12-150  
AR15-120/AR15-150/AR15-200  
AR20-150



Photo AR15-150